

INSTALLATION

RISE NOFIRNO Single & Multi Pipe Transits

Minimum Clearance Requirements	
Service Pipe Size O/D	Minimum Clearance between inside of conduit sleeve and service pipe
Upto & incl. 4" Service Pipes (Upto & incl. 114,3mm OD)	10 mm
Above 4" to & incl. 8" Service Pipes (Over 114,3mm and upto&incl.219,1 OD)	20 mm
Above 8" upto & incl. 12" Service Pipes (Over 219,1mm and upto & incl. 323,8 O/D)	30 mm
Above 12" upto & incl. 16" Service Pipes (Over 323,8mm and upto & incl. 406,4 O/D)	40 mm
Above 16" upto & incl. 20" Service Pipes (Over 406,4mm and upto & incl. 508 O/D)	60 mm
Above 20" upto & incl. 24" Service Pipes (Over 508mm and upto & incl. 609,6 OD)	90 mm
Above 24" upto & incl. 32" Service Pipes (Over 609,6 mm and upto & incl. 813,0 mm)	120 mm
Above 32" upto & incl. 36" Service Pipes (Over 813,0 mm and upto & incl. 914,0 mm)	150 mm
Above 36" upto & incl. 40" Service Pipes (Over 914,0 mm and upto & incl. 1016 mm)	180 mm

COMPONENTS

Item	Art.no	Item Description
NOFIRNO	500102	NOFIRNO SEALANT 310 ML CARTRIDGE
22/15-210 NOF-M	805073	22/15-210, MULTI-SLEEVE (10-PACK)
22/15-160 NOF-M	805074	22/15-160, MULTI-SLEEVE (10-PACK)
18/12-210 NOF-M	805054	18/12-210, MULTI-SLEEVE (10-PACK)
27/19-210 NOF-M	805064	27/19-210, MULTI-SLEEVE (10-PACK)
18/12-160 NOF-M	805053	18/12-160, MULTI-SLEEVE (10-PACK)
27/19-160 NOF-M	805063	27/19-160, MULTI-SLEEVE (10-PACK)

Consumables	Tools	
<ul style="list-style-type: none"> • Approved degreasing wipes • Cloths • Disposable nitrile gloves • Long nozzle • 45 deg. angle for cartridge nozzle 	<ul style="list-style-type: none"> • Water spray bottle x 2 • Sleeve cutting tool • Metal rule (150 mm) • Long nose pliers • Dead blow hammer • Wooden 20mm depth gauge 	<ul style="list-style-type: none"> • Head torch • High ratio (25:1) caulking gun • Air operated caulking gun

